

NOTE: The contents of this kit include a plug for the switch socket (Fig. 1). Some applications will require the use of an idle speed up control switch. For these applications, discard plug and install switch. For applications in which the original equipment hose does not have a switch socket the plug should be used. Install the plug into the socket making sure the plug is tightened securely so leakage will not occur (Fig. 2).

AVIS: Un bouchon pour la douille d'interrupteur ext inclus dans cette trousse (Fig. 1). Certaines applications exigent un manocontacteur de relenti. Dans ce cas, n'utilisez pas le bouchon mais installez l'interrupteur. Utilisez le bouchon dans le cas où le tuyau équipement d'origine n'a pas d'interrupteur. Installez le bouchon dans la douille. Assurez vous bien qu'il est bien serré pour éviter toutes fuites (Fig. 2).

NOTA: El contenido de este kit incluye un tapón para el zócalo de conmutación (Figura 1). Algunas aplicaciones requerirán el uso de un conmutador de control de velocidad de marcha. Para estas aplicaciones, extraiga el tapón e instale el conmutador de velocidad de marcha. Para estas aplicaciones, extraiga el tapón e instale el conmutador. Para aplicaciones en las que la manguera del equipo original no tenga un zócalo de conmutación, se deberá usar el tapón. Instale el tapón en el zócalo asegurándose de que el tapón esté seguramente ajustado para que no se produzcan pérdidas (Figura 2).




Fig. 1
Figura 1




Fig. 2
Figura 2

